

DECLARATION OF PERFORMANCE



N°: AXTERPOL P.4 SBS TALK/FMP NH 003 EN

1. Identification code AXTERPOL P.4 SBS TALK/FMP
2. Intended use Reinforced bitumen sheets for roof waterproofing
3. Manufacturer AXTER SAS
8, avenue Félix d'Hérelle
75016 PARIS
France
www.axter.eu/dop
4. Authorised representative NA
5. System of assessment and verification of constancy of performance of the product System 2+
- 6a. Product covered by the harmonised standard: EN 13707
The CSTB, notify body n° 0679 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0679 - CPR - 0128.
- 6b. European Technical Assessment : NA

7. Declared performance

Essential characteristics			Performance			Units	Harmonised technical specification
			Value	Tolerance			
				Min	Max		
Resistance to tearing (nail shank)	Longitudinal		200	100	-	N	EN 13707:2014
	Cross direction		200	100	-		
Tensile properties : maximum tensile force	Longitudinal		440	352	-	N/50 mm	
	Cross direction		440	352	-		
Tensile properties : elongation	Longitudinal		25	10	40	%	
	Cross direction		25	10	40		
Peel resistance of joint	Maximum force	Selvage	NA	-	-	N/50mm	
		End joint	NA	-	-		
	Average force	Selvage	NA	-	-		
		End joint	NA	-	-		
Shear resistance of joint	Maximum force	Selvage	NA	-	-	N/50mm	
		End joint	NA	-	-		
Flexibility at low temperature			-15	≤		°C	
Durability EN 1296	Flow resistance at elevated temperature		NA			°C	
Durability EN 1297	Visible defects		NA				
Resistance to impact			NA	≤		mm	
Resistance to static loading (method A)			NA	≥		kg	
Watertightness under 10 kPa			Conform			-	
Resistance to root penetration			NA			-	
Resistance to external fire exposure			F _{Roof} (Note 1)			-	
Reaction to fire			NPD			-	
Dangerous substances			Note 2 and 3			-	

NA: not applicable due to use of product.

Note 1 : As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared for the product alone.

Note 2 : This product does not contain asbestos or tar constituents

Note 3 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performances of the product identified above are in conformity with the declared performances.

In accordance with Regulation (UE)n°305/2011 , this declaration of performance is issued under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:
Peter Fleischmann (Managing Director)

Paris
06/01/2017

