

DECLARATION OF PERFORMANCE



N°: AXTERTOP EXTRA S5 MONT BLANC BESCHIEFERT NH 003 EN

1. **Identification code** AXTERTOP EXTRA S5 MONT BLANC BESCHIEFERT
2. **Intended use** Reinforced bitumen sheets for roof waterproofing
3. **Manufacturer** AXTER SAS
8, avenue Félix d'Hérelle
75016 PARIS
France
www.axter.eu/dop
4. **Authorised representative** NA
5. **System of assessment and verification of constancy of performance of the product** System 2+
- 6a. **Product covered by the harmonised standard:** EN 13707
The CSTB, notify body n° 0679 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0679 - CPR - 0128.
- 6b. **European Technical Assessment :** NA
7. **Declared performance**

Essential characteristics		Performance			Units	Harmonised technical specifications	
		Value	Tolerance				
			Min	Max			
Resistance to tearing (nail shank)	Longitudinal	NA	-	-	N	EN 13707:2014	
	Cross direction	NA	-	-			
Tensile properties : maximum tensile force	Longitudinal	980	800	1150	N/50 mm		
	Cross direction	900	800	1000			
Tensile properties : elongation	Longitudinal	50	35	65	%		
	Cross direction	55	35	70			
Peel resistance of joint	Maximum force	Selvedge	NA	-	N/50mm		
		End joint	NA	-			
	Average force	Selvedge	NA	-			-
		End joint	NA	-			-
Shear resistance of joint	Maximum force	Selvedge	NA	-	N/50mm		
		End joint	NA	-			-
Flexibility at low temperature		-30	≤		°C		
Durability EN 1296	Flow resistance at elevated temperature		NA	-	-		°C
Durability EN 1297	Visible defects		NA				
Resistance to impact		NA	≥		mm		
Resistance to static loading (method A)		NA	≥		kg		
Watertightness under 10 kPa		Conform			-		
Resistance to root penetration		NA			-		
Resistance to external fire exposure		F _{Roof} (Note 1)			-		
Reaction to fire		NPD			-		
Dangerous substances		Note 2 and 3			-		

NA: not applicable due to use of product.

Note 1 : As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared for the product alone.

Note 2 : This product does not contain asbestos or tar constituents

Note 3 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performances of the product identified above are in conformity with the declared performances.

In accordance with Regulation (UE)n°305/2011 , this declaration of performance is issued under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:
Peter Fleischmann (Managing Director)

Paris
06/01/2017

