

DECLARATION OF PERFORMANCE



N°: COLETANCHE XPC HFA NH 001 EN

- 1. Identification code** COLETANCHE XPC HFA
- 2. Intended use**
 Geosynthetic barriers use in the construction of reservoirs and dams
 Geosynthetic barriers use in the construction of canals
 Geosynthetic barriers use as a fluid barrier in the construction of tunnels and underground structures
 Geosynthetic barriers use as a fluid barrier in the construction of liquid waste disposal sites or transfer sites
 Geosynthetic barriers use in the construction of solid waste storage and disposal sites
 Geosynthetic barriers use in transportation infrastructure
- 3. Manufacturer**
 AXTER SAS
 143, avenue de Verdun
 92130 Issy-les-Moulineaux
 France
 www.axter.eu/dop
- 4. Authorised representative** NA
- 5. System of assessment and verification of constancy of performance of the product** System 2+
- 6a. Product covered by the harmonised standard:** EN 13361, EN 13362, EN 13491, EN 13492, EN 13493, EN 15382
 The ASQUAL, notify body n° 0334 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0334 - CPR - 0011.
- 6b. European Technical Assessment :** NA
- 7. Declared performance**

Essential characteristics			Performance			Harmonised technical specification	
			Value	Tolerance			Units
				Min	Max		
Tensile properties : maximum tensile force	Longitudinal		950	750		EN 13361:2005/A1:2006 EN 13362:2006 EN 13491:2005/A1:2006 EN 13492:2005/A1:2006 EN 13493:2006 EN 15382:2013	
	Cross direction		800	630			
Tensile properties : elongation	Longitudinal		35	25			%
	Cross direction		35	25			
Static puncture test (CBR test)	Resistance		2,7	2,4			kN
	Move		50	40			mm
Permeability to liquids			< 1.10 ⁻⁶				m ³ /m ² /j
Resistance to oxidation	Residual value of tensile strength	Maximum tensile force	100	75			%
		Elongation	100	75			
Resistance to weathering		Maximum tensile force	100	75			%
		Elongation	100	75			
Dangerous substances			Note 1 and 2			-	
Gas Permeability			< 2.10 ⁻⁴			m ³ /(m ² .j.atm)	

NA: not applicable due to use of product.

Note 1 : This product does not contain asbestos or tar constituents

Note 2 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performances of the product identified above are in conformity with the declared performances.

In accordance with Regulation (UE)n°305/2011 , this declaration of performance is issued under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:
 Peter Fleischmann (Managing Director)

Paris
 24/03/2020

