

DECLARATION OF PERFORMANCE



N°: FORCE 4000 TRAFIC NT NH 003 EN

- 1. Identification code** FORCE 4000 TRAFIC NT
- 2. Intended use** Reinforced bitumen sheets for roof waterproofing
Reinforced bitumen sheets for waterproofing of concrete bridge decks and other trafficked areas of concrete
- 3. Manufacturer** AXTER SAS
8, avenue Félix d'Hérelle
75016 PARIS
France
www.axter.eu/dop
- 4. Authorised representative** NA
- 5. System of assessment and verification of constancy of performance of the product** System 2+
- 6a. Product covered by the harmonised standard:** EN 13707
The CSTB, notify body n° 0679 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0679 - CPR - 0128.
EN 14695
The ASQPE, notify body n° 1683 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 1683 - CPR - 0020.
- 6b. European Technical Assessment :** NA

7. Declared performance

Essential characteristics		Performance				Units	Harmonised technical specification
		Value	Tolerance				
			Min	Max			
Tensile properties : maximum tensile force	Longitudinal	900	800	-	N/50 mm	EN 13707:2014 EN 14695:2010	
	Cross direction	900	800	-			
Tensile properties : elongation	Longitudinal	45	35	-	%		
	Cross direction	50	40	-			
Flexibility at low temperature		-16	≥		°C		
Durability EN 1296	Flow resistance at elevated temperature		90	≥			°C
Dangerous substances		Note 2 and 3					-
Resistance to tearing (nail shank)	Longitudinal	NA	-	-	N		
	Cross direction	NA	-	-			
Peel resistance of joint	Maximum force	Selvage	NA	-	N/50mm		
		End joint	NA	-			
	Average force	Selvage	NA	-			
		End joint	NA	-			
Shear resistance of joint	Maximum force	Selvage	900	800	N/50mm		
		End joint	900	800			
Durability EN 1297	Visible defects		NA				
Resistance to impact		1750	≥		mm		
Resistance to static loading (method A)		25	≥		kg		
Watertightness under 10 kPa		Conform			-		
Resistance to root penetration		Conform			-		
Resistance to external fire exposure		F _{Roof} (Note 1)			-		
Reaction to fire		NPD			-		
Water absorption		2	≤		%		
Durability EN 1296	Flexibility at low temperature		Decrease after ageing ≤ 15°C		°C		
Resistance to dynamic water pressure		Conform			-		
Resistance to compaction of an asphalt layer		Conform			-		
Behaviour of bitumen sheets during application of mastic asphalt		NA			%		
Crack bridging ability		NPD			-		
Performance characteristics with VERNIS ANTAC GC							
Bond strength		0,5	≥		N/mm ²		
Shear strength		0,1	≥		N/mm ²		
Compatibility by heat conditioning		100	≥		%		

NA: not applicable due to use of product.

Note 1 : As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared for the product alone.

Note 2 : This product does not contain asbestos or tar constituents

Note 3 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performances of the product identified above are in conformity with the declared performances.

In accordance with Regulation (UE)n°305/2011 , this declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Peter Fleischmann (Managing Director)

Paris
11/06/2018

