

# DECLARATION OF PERFORMANCE



N°: PYE PV 200 DD NHD 001 EN

1. Identification code PYE PV 200 DD
2. Batch number allowing identification of the construction product Refer to the product label
3. Intended use Reinforced bitumen sheets for roof waterproofing  
Bitumen damp proof sheets including bitumen basement tanking sheets
4. Manufacturer AXTER SAS  
8, avenue Félix d'Hérelle  
75016 PARIS  
France  
www.axter.eu/dop
5. Authorised representative NA
6. System of assessment and verification of constancy of performance of the product System 2+
7. Product covered by the harmonised standard: EN 13707  
Kiwa MPA Bautech GmbH, notify body n° 2007 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 2007-CPR-D.4289-I/2013.  
EN 13969  
Kiwa MPA Bautech GmbH, notify body n° 2007 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 2007-CPR-B.4289-II/2013.
8. European Technical Assessment : NA
9. Declared performance

Essential characteristics			Performance			Harmonised technical specification
			Value	Tolerance		
				Min	Max	
Resistance to tearing (nail shank)	Longitudinal		NPD	≥		N
	Cross direction		NPD	≥		
Tensile properties : maximum tensile force	Longitudinal		1000	≥		N/50 mm
	Cross direction		1000	≥		
Tensile properties : elongation	Longitudinal		2	≥		%
	Cross direction		2	≥		
Shear resistance of joint	Maximum force	Selvedge	NPD	≥		N/50mm
		End joint	NPD	-	-	
Flexibility at low temperature			-25	≤		°C
Resistance to impact			NPD	≥		mm
Reaction to fire			E			-
Dangerous substances			Note 2 and 3			-
Peel resistance of joint	Maximum force	Selvedge	NPD	≥		N/50mm
		End joint	NPD	≥		
	Average force	Selvedge	NPD	≥		
		End joint	NPD	≥		
Resistance to static loading (method A)			NPD	≥		kg
Durability EN 1296	Flow resistance at elevated temperature		100			°C
Durability EN 1297	Visible defects		NPD			
Watertightness under 10 kPa			Conform			-
Resistance to root penetration			NPD			-
Resistance to external fire exposure			FRoof (Note 1)			-
Resistance to static loading (method B)			NPD	≥		kg
Watertightness under 60 kPa			Conform			-
Durability EN 1296	Watertightness		NPD			-
Durability EN 1847	Watertightness		NPD			-

NA: not applicable due to use of product.

Note 1 : As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared for the product alone.

Note 2 : This product does not contain asbestos or tar constituents

Note 3 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:  
Peter Fleischmann (Managing Director)

Paris  
July 1, 2013

