

# DECLARATION OF PERFORMANCE



N°: SAMTOR 180 NHI 002 EN

1. Identification code SAMTOR 180
2. Intended use Feuilles bitumineuses armées pour l'étanchéité de toiture
3. Manufacturer AXTER SAS  
8, avenue Félix d'Hérelle  
75016 PARIS  
France  
www.axter.eu/dop
4. Authorised representative NA
5. System of assessment and verification of constancy of performance of the product System 2+
- 6.a Product covered by the harmonised standard: EN 13707 : 2014  
The CSTB, notify body n° 0679 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0679 - CPR - 0128.
- 6.b European Technical Assessment : NA
7. Declared performance

Essential characteristics			Performance			Harmonised technical specifications	
			Value	Tolerance			Units
				Min	Max		
Resistance to tearing (nail shank)	Longitudinal	NA	-	-	N	EN 13707+A2:2014	
	Cross direction	NA	-	-			
Tensile properties : maximum tensile force	Longitudinal	600	550	-	N/50 mm		
	Cross direction	500	450	-			
Tensile properties : elongation	Longitudinal	40	30	-	%		
	Cross direction	40	30	-			
Peel resistance of joint	Maximum force	Selvage	NA	-	-		N/50mm
		End joint	NA	-	-		
	Average force	Selvage	NA	-	-		
		End joint	NA	-	-		
Shear resistance of joint	Maximum force	Selvage	NA	-	-		N/50mm
		End joint	NA	-	-		
Flexibility at low temperature			5	≤	°C		
Durability EN 1296	Flow resistance at elevated temperature		NA	-	-		°C
Durability EN 1297	Visible defects		NA	-	-		
Resistance to impact			NA	≤	mm		
Resistance to static loading (method A)			NA	≥	kg		
Watertightness under 10 kPa			Conform		-		
Resistance to root penetration			NA		-		
Resistance to external fire exposure			NPD		-		
Reaction to fire			F		-		
Dangerous substances			Note 2 and 3		-		

NA: not applicable due to use of product.

Note 1 : As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared for the product alone.

Note 2 : This product does not contain asbestos or tar constituents

Note 3 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performances of the product identified above are in conformity with the declared performances.

In accordance with Regulation (UE)n°305/2011 , this declaration of performance is issued under the sole responsibility of the manufacturer identified

Signed for and on behalf of the manufacturer by:  
Peter Fleischmann (Managing Director)

Paris  
06/01/2017

